



PUMPLETTER
MARCH 04, 2011

AODD Pumps for Adhesive Backing Application

PRODUCT TYPE AND ENVIRONMENT MUST BE CONSIDERED WHEN CHOOSING THE PROPER PUMP

Neoflux Introduces AODD Pump for Adhesive Backing Application

The **nf25** Metal Air-Operated Double-Diaphragm (AODD) pump from Neoflux features performance versatility, such as the attachment of a Poluene Coating to Paper Products.

Neoflux's nf25 Series AODD pump is 1" with Wetted Housings, Liquid chambers and Manifolds which are constructed of Die-Cast Graded Aluminum. The AODD pump is available with **Neo-Tef** PTFE elastomers, making it ideal for the safe and efficient handling of adhesive backing.

The pump offers flow rates up to 210 LPM (55 GPM) and can handle pressures up to 8.6 bar (125 psi). The **nf25** Series AODD pump has maximum suction-lift capabilities of 4.6 Meter for dry products and 9.0 Meter for wet products, while being able to handle solids with diameters reaching 3 mm. Elastomer options include Buna-N and Neoprene.

The **nf25** Series AODD pumps are equipped with Neoflux's *Neo-Flo* air distribution system (ADS). The **nf25** Series AODD pump has an externally serviceable air-valve body that is attached to the center block. Built-in air-valve tolerances allow for the passage of some moisture and air-line particulates, allowing free movement of the air valve.

For Further Information, Please visit www.neoflux.in Or Contact

Neoflux Technic Private Limited

43, GIDC Industrial Estate, Phase – I,
Vatva, Ahmedabad – 380018, Gujarat, INDIA

Contact # +91 - 9825009234
Email – info@neoflux.in



We look forward to being of assistance in your process equipment requirements.

It all flows free at [neoflux.in](http://www.neoflux.in).....

***Visit us at www.neoflux.in and get free access
to exclusive content & Pumperletter***